AUTOMATIC AIR VENT

PN16 F9516
PN25 F9525

FEATURES & SPECIFICATIONS

- Anti corrosion treatment for internal parts to prevent from the valve rusting
- Large venting capacity
- Air tight
- Available in 15, 20 & 25mm inlet diameter threaded BSPT




PRESSURE & TEMPERATURE RATINGS

Working Pressure	16bar	25bar
Test Pressure (x1.5)	24bar	37.5bar
Working Temperature	-20°C ... 120°C	
Suitable Media	Water	

MATERIAL SPECIFICATIONS

Part	Material	Specification
Body	Ductile Iron	BS EN1563 EN-GJS-450-10
Plug	Stainless Steel 304	EN 10088-3 1.4301
Bonnet	Ductile Iron	BS EN1563 EN-GJS-450-10
Sealing Seat	Bronze	EN 1982 GC CC491K
Sealing Washer	Viton EPDM	BS EN ISO 1629 Commercial
Sealing Plug	Viton	BS EN ISO 1629
Yoke	Stainless Steel 304	EN 10088-3 1.4301
Pin	Stainless Steel 304	EN 10088-3 1.4301
Arm	Stainless Steel 304	EN 10088-3 1.4301
Bolt	Steel	BS970 Part1 080A15
Screw	Stainless Steel 304	EN 10088-3 1.4301
Snap Ring	Stainless Steel 201	EN 10088-3 1.4372
O-Ring	Viton EPDM	BS EN ISO 1629 Commercial
Ball	Stainless Steel 304	EN 10088-3 1.4301
Spring Washer	Steel	BS970 Part1 080A15
Flat Washer	Steel	BS970 Part1 080A15



DIMENSIONS

(mm)

DN mm	DN inch	Inlet	Outlet	Orifice	L	H
15	½	15	15	1.6	134	140
20	¾	20	15	1.6	134	140
25	1	25	15	1.6	134	140

Fivalco reserves the right to alter the information in this document without prior notice. Fivalco shall not be liable for technical errors or omissions contained herein.
Images are for illustrative purposes only. Refer to local sales representatives for detail catalogues, technical data and specifications.



We deliver quality product packages and solutions at nano speed