NRS RESILIENT SEAT GATE VALVE

PN16 V23A16
PN25 F23A25

FEATURES & SPECIFICATIONS

- Non-rising stem
- Inside screw
- Bolted bonnet
- Resilient seat for pipeline isolation
- Durable fusion bonded epoxy coated
- Comply with BS 5163 / EN 1074-2
- Square cap option available
- Flange drilled to BS 4504 PN16 / EN 1092-2 PN16 / BS 4504 PN25 / EN 1092-2 PN25 /ANSI Class 150 (Specify on order)
- WRAS approved option available upon request
- Applicable for Building Services, Air-Conditioning, Fire Protection, Cold Water Plumbing, Hot Water System, Water Supply Works, Water Treatment Plant, General Industries




PRESSURE & TEMPERATURE RATINGS

Working Pressure	16bar	25bar
Shell Test Pressure (x1.5)	24bar	37.5bar
Seat Test Pressure (x1.1)	17.6bar	27.5bar
Working Temperature	-10°C ... 80°C	
Suitable Media	Water	

MATERIAL SPECIFICATIONS

Part	Material	Specification
Body	Ductile Iron	BS EN1563 EN-GJS-450-10
Cover	Ductile Iron	BS EN1563 EN-GJS-450-10
Disc	EPDM coated DI	BS EN1563 EN-GJS-450-10
Stem Nut	Brass Ductile Iron	EN 12165 CW617N BS EN1563 EN-GJS-450-10
Stem	Stainless Steel 420	BS970 420S29
Card Block	Brass Carbon Steel	EN 12165 CW617N BS970 Part1 080A15
O-Ring	NBR	Commercial
Seal	EPDM	Commercial
Bolt	Carbon Steel	BS970 Part1 080A15
Handwheel	Ductile Iron	BS EN1563 EN-GJS-450-10



DIMENSIONS

(mm)

DN (mm)	50	65	80	100	125	150	200	250	300	350	400	450	500	600
DN (inch)	2	2½	3	4	5	6	8	10	12	14	16	18	20	24
L	178	190	203	229	254	267	292	330	356	381	406	432	457	508
H (PN16)	224	228	272	314	365	405	515	600	667	783	900	995	1078	1242
H (PN25)	227	230	270	310	365	406	512	580	657	783	900	-	-	-
A	160	160	180	200	250	250	300	350	400	500	500	500	600	600

Notes : PN25 only available for size DN50 ... DN400.

Fivalco reserves the right to alter the information in this document without prior notice. Fivalco shall not be liable for technical errors or omissions contained herein.
Images are for illustrative purposes only. Refer to local sales representatives for detail catalogues, technical data and specifications.