HIGHRISER BUTTERFLY VALVE WAFER TYPE

300PSI Fig No.: FPBG-300W

FEATURES & SPECIFICATIONS

- Valve conforms to MSS SP-67 / BS EN593: 2009
- Design and test standard conforms to FM1112 and UL1091
- Fusion bonded epoxy coated RAL3002
- Fitted with visual indicator and supervisory switch
- EPDM encapsulated disc
- Valve suitable for indoor and outdoor installation
- Universal wafer connection suitable for ANSI Class 150 / BS 4504 PN16 / EN1092-2 PN16
- Working pressure : 300psi - Non Shock Coldwater
  Max. Test Pressure : 600psi
- Working temperature : -10°C ... 120°C




c UL us LISTED

FM APPROVED

MATERIALS LIST

Name	Material
Body	Ductile Iron ASTM A536 65-45-12
Disc	Ductile Iron ASTM A536 65-45-12 + EPDM
Lower Shaft	Stainless Steel SS410
Upper Shaft	Stainless Steel SS410
Signal Gearbox	Ductile Iron ASTM A536 65-45-12
O-Ring	EPDM
Bushing	Bronze ASTM B150M C63000
Gland	Galvanized Carbon Steel Surface Passivation
Washer	Galvanized Carbon Steel Surface Passivation
Plug	Galvanized Carbon Steel Surface Passivation
Gear Box Fasteners	Galvanized Carbon Steel Surface Passivation



DIMENSIONS (inch/mm)

Size	2"/50	2.5"/65	3"/80	4"/100	5"/125	6"/150	8"/200	10"/250	12"/300
A	140.5	152.5	157.5	176	191	202.5	243.5	273	311
B	77	80	87	108	132	144	174	208	261
C	110	110	110	110	133	133	187	187	187
H	262.4	274.5	279.5	298	313.5	330	379	409	465
L	43	46	46	52	56	56	62	68	78
L1	47	51	51	57	61	61	67	73	83
ΦD	82	97	109	140	165	198	252	304	355
ΦE	108	108	108	108	150	150	250	250	250

NET WEIGHT (kg) & CRATE QTY (pcs)

Size	2"/50	2.5"/65	3"/80	4"/100	5"/125	6"/150	8"/200	10"/250	12"/300
N.W.	4.6	4.9	4.9	6.1	10.3	12.2	22.9	28.7	46.5
Crate Qty	95	85	75	60	50	40	25	15	15

Fivalco reserves the right to alter the information in this document without prior notice. Fivalco shall not be liable for technical errors or omissions contained herein.
Images are for illustrative purposes only. Refer to local sales representatives for detail catalogues, technical data and specifications.